



VIEWHUB FEATURES

11/27/2017 / REV04

Feature	ViewHub	ViewHub Pro	ViewHub Pro I	ViewHub Pro II
T1V device	CX-01-VH	CX-03-VHP-4K	CX-03-VHPI	CX-03-VHPPII
Maximum video touchwall size, resolution	Single or Dual Screens, 1080p	3840x2160 output over a single DisplayPort connection	up to 4 1080p outputs with a max resolution of 3840x2160	up to 8 1080p outputs with a max resolution of 7680x2160
AirConnect™ device sharing/mirroring on Windows, OS X, iOS, and Android	unlimited devices can connect; up to 4 devices can live broadcast on 1080p screen, up to 16 devices can live broadcast on 4K screen	unlimited devices can connect; up to 4 devices can live broadcast on 1080p screen, up to 16 devices can live broadcast on 4K screen	unlimited devices can connect; up to 4 devices can live broadcast on 1080p screen, up to 16 devices can live broadcast on 4K screen	unlimited devices can connect; up to 4 devices can live broadcast on 1080p screen, up to 16 devices can live broadcast on 4K screen
Live streaming devices	stream 1080p at 30 fps with synchronized audio	stream 1080p at 30 fps with synchronized audio	stream 1080p at 30 fps with synchronized audio	stream 1080p at 30 fps with synchronized audio
Built in Protocol	Airplay + T1V AirConnect			
Bandwidth per live stream (T1V AirConnect)	typical 300 kb/s Max 3 mb/s			
Bandwidth per live stream (AirPlay)	typical 300 kb/s Max 11mb/s			
Wireless device connectivity	toggle between users via app			
Direct Network Mode	✓	✓	✓	✓
World Network Mode	✓	✓	✓	✓
Hardline inputs	up to 1*	up to 4*	up to 4*	up to 4*
AirConnect Access™ - View, Control, Point on ViewHub display	View/Point Only	View/Point Only	View/Point Only	View/Point Only
AirConnect Files™ - Share Notes / URLs / Files to ViewHub; Download from ViewHub	✗	✗	✗	✗
AirConnect™ video conferencing (2018 release)	✓*	✓*	✓*	✓*

*optional add-ons; additional fees may apply