

PRODUCT SPECIFICATION SHEET

ThinkHub[®]PRO

For use with single 4K or 5K displays

ThinkHub consolidates the moving pieces of teamwork - devices, applications, people, ideas, and content - to revolutionize your ability to achieve great work, together. Whether you're giving a presentation, running a brainstorming session, or strategizing with your team - use ThinkHub to engage with your peers and cultivate exceptional work anytime, anywhere.


| | |
|---|---|
| SKU | CX-07M2M-THP-B |
| Target Applications | |
| | Classrooms Huddle Spaces Briefing Centers Board Rooms Design Centers Training Rooms Executive Offices Libraries |
| Room Types | |
| Room Size | Small to Medium (2-10 people) |
| Technical Specifications | |
| Dimensions (W x H x D) | 26in x 14in x 3.8in |
| Weight | 40 lbs |
| Resolutions | 3840 x 2160 @ 60Hz 5120 x 2160 @ 60Hz |
| Power Consumption | Max: 370 W |
| Thermal Output | Max: 1262 BTU/h |
| Storage / RAM | 512GB / 32GB |
| Processor + GPU | Apple M2 Max with 12-core CPU, 30-core GPU, 16-core Neural Engine |
| Network | Wired 1Gbps (preferred) Optional Wi-Fi 802.11ac / 802.11 a/b/g/n |
| Built-in Protocol | AirPlay and T1V app |
| I/O | USB 3.0 (5) (1) Ethernet 1000 Base-T; (2) RJ45 control ports 3.5mm Stereo Out up to (2) HDMI output 4k 60hz 4:4:4 (4) Optional Hardline Inputs* |
| * hardline inputs accept 720p and 1080p video sources, which will be viewed at 1080p @30 Hz | |
| Hardware Warranty | 2 years |
| BYOD Connectivity | |
| AirPlay | macOS / iOS platforms |
| Required bandwidth per live stream | typical: 300 kb/s max: 11 mb/s |
| Streaming Media | Stream 1080p at 30fps w/synchronized audio (iOS) |
| T1V app | macOS, iOS, Windows, Android, Linux platforms |
| Required bandwidth per live stream | typical: 300 kb/s max: 3 mb/s |
| Streaming Media | Stream 1080p at 30fps w/synchronized audio (macOS, Windows) |
| User Capacity | 50 simultaneous participants |
| Wireless Device Connectivity | No dongle needed; toggle between users via the T1V app |
| TouchControl™ | Unlimited TouchControl™ device remote control on Windows, macOS |
| Network Modes | Direct Mode: Compatible with a single subnet and/or multiple subnets World Mode: Developed for environments where Direct Mode is not possible (due to network architecture or security restraints) |



CPU module with included mounting system



Bottom panel mounts



Side panel mounts

