## ThinkHub.pro

For use with single/dual 4K displays, or single 5K

ThinkHub consolidates the moving pieces of teamwork - devices, applications, people, ideas, and content - to revolutionize your ability to achieve great work, together. Whether you're giving a presentation, running a brainstorming session, or strategizing with your team - use ThinkHub to engage with your peers and cultivate exceptional work anytime, anywhere.

SKU	CX-07M2U-THP
Target Applications	
Room Types	Classrooms   Huddle Spaces   Briefing Centers   Board Rooms   Corporate Lobbies   Design Centers   Training Rooms   Executive Offices   Libraries   Innovation Labs
Room Size	Medium to Large (3-25+ people)
Display Requirements	
Display Resolution (W x H)	up to (4) 3840 x 2160
	up to (2) 5120 x 2160
ThinkHub Device	
Dimensions (W x H x D)	19in x 5.25in x 15in (3RU)
Weight	20 lbs
Power Consumption	Max: 370 W
Thermal Output	Max: 1262 BTU/h
Storage / RAM	512GB / 32GB
Processor + Graphics	Apple M2 Ultra with 24-core CPU, 60-core GPU, 32-core Neural Engine
Network	Wired 1Gbps (preferred)
	Optional Wi-Fi 802.11ac / 802.11 a/b/g/n
Built-in Protocol	AirPlay and T1V app
1/0	USB 3.0 (5)
	(1) Ethernet 1000 Base-T; (2) RJ45 control ports
	RCA Stereo Out
	up to (4) HDMI output 4k 60hz 4:4:4
	(12) Optional Hardline Inputs*
	( ) - F

ThinkHub Device

\*Video / USB extenders sold separately





\* hardline inputs accept 720p and 1080p video sources, which will be viewed at 1080p @30 Hz

Hardware Warranty	2 years	
BYOD Connectivity		
AirPlay	macOS / iOS platforms	
Recommended bandwidth	typical: 300 kb/s	
per live stream	max: 11 mb/s	
Streaming Media	Stream 1080p at 30fps w/synchronized audio (iOS)	
T1V app	macOS, iOS, Windows, Android, Linux platforms	
Recommended bandwidth	typical: 300 kb/s	
per live stream	max: 3 mb/s	
Streaming Media	Stream 1080p at 30fps w/synchronized audio (macOS, Windows)	
User Capacity	50 simultaneous participants	
Wireless Device Connectivity	No dongle needed; toggle between users via the T1V app	
TouchControl™	Unlimited TouchControl™ device remote control on Windows, macOS	
Network Modes	Direct Mode: Compatible with a single subnet and/or multiple subnets	
	World Mode: Developed for environments where Direct Mode is not possible (due to network architecture or security restraints)	

