PRODUCT SPECIFICATION SHEET

ThinkHub.

85" 4K with ThinkHub Pro

ThinkHub consolidates the moving pieces of teamwork - devices, applications, people, ideas, and content - to revolutionize your ability to achieve great work, together. Whether you're giving a presentation, running a brainstorming session, or strategizing with your team - use ThinkHub to engage with your peers and cultivate exceptional work anytime, anywhere.

SKU	WX-OT5AV-07M2M-85-THP
Target Applications	
Room Types	Classrooms Huddle Spaces Briefing Centers Board Rooms Design Centers Training Rooms Executive Offices Libraries
Room Size	Small to Medium (2-10 people)
Technical Specifications (Display)	
Display Resolution (W x H)	3840 x 2160 @ 60Hz
Video Input	1 x HDMI 2.0
Dimensions (W x H x D)	75.96 x 44.82 x 4.61 in
Weight	201.28 lbs
Brightness	500 (cd/m2)
Power Consumption	480 W Max
Operating Temperature	0 C - 40 C
Touch Technology	InGlass™ Intelligent touch
Glass	2 mm Optically Bonded, Anti-Glare, Anti-Fingerprint Glass
VESA pattern	600mm x 400mm
Audio	4 x 10W

Technical Specifications (ThinkHub Device)		
Dimensions (W x D x H)	19in x 5.25in x 15in (3RU)	
Weight	20 lbs	
Resolution	Portrait: up to 2160x3840 @ 60hz, Landscape: up to 3840x2160 @ 60hz	
Power Consumption	Max: 370 W	
Thermal Output	Max: 1262 BTU/h	
Storage / RAM	512GB / 32GB	
Processor + Graphics	Apple M2 Max with 12-core CPU, 30-core GPU, 16-core Neural Engine	
Network	Wired 1Gbps (preferred)	
	Optional Wi-Fi 802.11ac / 802.11 a/b/g/n	
Built-in Protocol	T1V app	
l/Ο	USB 3.0 (5)	
	(1) Ethernet 1000 Base-T; (2) RJ45 control ports	
	RCA Stereo Out	
	up to (2) HDMI output 4k 60hz 4:4:4	

(8) Optional Hardline Inputs*

* hardline inputs accept 720p and 1080p video sources, which will be viewed at 1080p @30 Hz Hardware Warranty 2 years

BYOD Connectivity

T1V app	macOS, iOS, Windows, Android, Linux platforms
Required bandwidth	typical: 300 kb/s
per live stream	max: 3 mb/s
Streaming Media	Stream 1080p at 30fps w/synchronized audio (macOS, Windows
User Capacity	50 simultaneous participants
Wireless Device Connectivity	No dongle needed; toggle between users via the T1V app
TouchControl™	Unlimited TouchControl [™] device remote control on Windows, macOS
Network Modes	Direct Mode: Compatible with a single subnet and/or multiple subnets
	World Mode: Developed for environments where Direct Mode is not possible (due to network architecture or security restraints)



· · · 2



Rack Module



